



COMBO PRESS & PULL

#CSPB

WARANTY:

Limited 15-year warranty against manufacturers defect on steel posts, welds, bars and other steel parts.

PRODUCT SPECIFICATION:

TriActive USA's CSPB assumes usage of American standard size tubing, namely 4" x 4" square tubing x 11ga, 1-1/2" x 3" rectangular tubing x 11ga, 1-1/2" Sch. 40 pipe, 1-1/4" OD round tubing x 11ga, 1/4" hot rolled flat bar, 1-1/2" OD round tubing x 14ga, 1/8" square sheet metal seats and back rests. TriActive USA Fitness Equipment does not include any of the following: exposed cables, hydraulics or plastic seating.

POWDER COATING SPECIFICATION:

Powder coating thickness 6-8 mils. Coatings are tested for 1000 hours of salt spray resistance. Pre-treated, iron phosphate applied, zinc powder applied, functional powder applied, and final TGIC powder coat is applied to provide outstanding weathering capabilities.



*ACTUAL EQUIPMENT MAY LOOK DIFFERENT THAN SHOWN DUE TO FREQUENT DESIGN UPGRADES. THIS EQUIPMENT IS DESIGNED FOR INDIVIDUALS WEIGHING UP TO 330 LBS.



SAFE & SECURE



WEATHER RESISTANT



TAMPER PROOF

DIMENSIONS:

78" L X 36" W X 70" H

WEIGHT:

280 LBS

COLOR:

GREEN OR BLUE

ASSEMBLY:

NOT REQUIRED