



TriActive
— USA —

11821 SLAUSON AVE
SANTA FE SPRINGS, CA 90670
800-509-0597
TRIACTIVEUSA.COM

HORIZONTAL LADDER

WARRANTY:

Limited 10-year warranty on steel posts, welds, bars and other steel parts on all units that are fully welded, with no moving parts.

PRODUCT SPECIFICATION:

The HLAD is constructed using American standard-size structural steel components, including 4" x 4" square tubing with a 1/4" wall thickness for the main posts; 2" x 2" square tubing with a .120" wall thickness for the ladder side rails and gussets; Ø1.25" round tubing with a .120" wall thickness for the ladder rungs; and Ø2" round tubing with a .120" wall thickness for the cross members. Construction also incorporates 14" x 14" x 1/2" thick steel base plates, 5/16" thick mounting brackets, and 1/4" thick main beam gussets. Connections utilize 1/2"-13 18-8 stainless steel square-neck carriage bolts with tamper-resistant breakaway nuts.

POWDER COATING SPECIFICATION:

Powder coating thickness 6-8 mils. Coatings are tested for 1000 hours of salt spray resistance. Pre-treated, iron phosphate applied, zinc powder applied, functional powder applied, and final TGIC powder coat is applied to provide outstanding weathering capabilities.

#HLAD



*ACTUAL EQUIPMENT MAY LOOK DIFFERENT THAN SHOWN DUE TO FREQUENT DESIGN UPGRADES. THIS EQUIPMENT IS DESIGNED FOR INDIVIDUALS WEIGHING UP TO 330 LBS.



SAFE & SECURE



WEATHER RESISTANT



TAMPER RESISTANT

DIMENSIONS:

139"L X 61"W X 98"H

WEIGHT:

672 LBS

COLOR:

GREEN OR BLUE

ASSEMBLY:

REQUIRED